

THE REFRESH

PASSION SPAS PURE COLLECTION









SPECIFICATIONS/GENERAL

| Dimensions Lx Wx H | 204 x 204 x 85 cm |
|-------------------------------|---|
| Number of Seats | 4 |
| Number of Loungers | |
| Capacity in Liter | 1380 |
| Dry Weight in kg | 250 |
| Full Weight in kg | 1630 |
| | Aristech® Acrylic with Vinylester and Polyester |
| Synthetic Maintenance F | ree CabinetStandard |
| Removable Side Panels | 4 |
| Cabinet Material | Synthetic |
| Durable Support System | 1Synthetic |
| Everlast TM Full Floor Su | pport MaterialPolyester |
| High Density Urethane I | nsulationStandard |
| | |

WATER SYSTEM

| Total jets34 | | |
|--|--|--|
| Water Jets, Stainless Steel26 | | |
| Air Injector Jets8 | | |
| Air Control Valve3 | | |
| Filters / Surface(1) 50 Square Feet | | |
| Side Access Skim FilterHigh-Volume Side Load Skimmer | | |
| Floor Drain | | |
| External DrainI | | |
| Hi Flow Suctions2 | | |
| 5"Massage Jets, Directional, Rotational and Pulsational5 | | |
| 3"Directional Jets9 | | |
| 2"Directional JetsII | | |
| Ozone Jets | | |
| | | |

SPECIAL FEATURES

| | Soft Air Massage System | Standard | |
|------------------------------|--|----------|--|
| | Molded Headrest Soft Pillows with LED Light | | |
| | StarBrite Interior LED Light System | Standard | |
| | Water Fall with LED | | |
| | Cascade Creek Water Fall | l | |
| Exterior Corner LED Lighting | | | |
| | Aromatherapy System | Standard | |
| Ozone Sanitation SystemS | | Standard | |
| | Ultra Efficient Dual-Wrap Cabinet Insulation | Standard | |
| | 5/4 Ultra Efficient Walk-On Cover | Standard | |
| | | | |

PUMP INFORMATION

| Massage Pump 1:LX LP300 | 2,2 kW |
|----------------------------|--------|
| Filtration Pump: LX WTC50M | |
| Air Pump: LX AP300 | 300 W |

ELECTRICAL SYSTEM

| Voltage | 230 V |
|------------------------------|-----------------|
| Amperage | |
| Full Flow Electric Heater | 3 kW |
| Control System | Balboa VS510DZ |
| Light (18 x Multi Color LED) | |
| Electronic Topside Control | Balboa VL80 I D |